

# MDF7N65B

## N-Channel MOSFET 650V, 7.0A, 1.35Ω

### General Description

These N-channel MOSFET are produced using advanced MagnaChip's MOSFET Technology, which provides low on-state resistance, high switching performance and excellent quality.



These devices are suitable device for SMPS, high Speed switching and general purpose applications.

### Features

- $V_{DS} = 650V$
- $I_D = 7.0A$
- $R_{DS(ON)} \leq 1.35\Omega$  @  $V_{GS} = 10V$
- $R_{DS(ON)} \leq 1.35\Omega$  @  $V_{GS} = 10V$

### Applications

- Power Supply
- PFC
- High Current, High Speed Switching


 TO-220F  
MDF Series


### Absolute Maximum Ratings ( $T_a = 25^\circ C$ )

Characteristics		Symbol	Rating	Unit
Drain-Source Voltage		$V_{DSS}$	650	V
Gate-Source Voltage		$V_{GSS}$	$\pm 30$	V
Continuous Drain Current	$T_c=25^\circ C$	$I_D$	7.0*	A
	$T_c=100^\circ C$		4.4*	A
Pulsed Drain Current <sup>(1)</sup>		$I_{DM}$	28*	A
Power Dissipation	$T_c=25^\circ C$	$P_D$	42	W
	Derate above 25 °C		0.33	W/°C
Repetitive Avalanche Energy <sup>(1)</sup>		$E_{AR}$	13.1	mJ
Peak Diode Recovery dv/dt <sup>(3)</sup>		dv/dt	4.5	V/ns
Single Pulse Avalanche Energy <sup>(4)</sup>		$E_{AS}$	212	mJ
Junction and Storage Temperature Range		$T_J, T_{stg}$	-55~150	°C

\* Id limited by maximum junction temperature

### Thermal Characteristics

Characteristics	Symbol	Rating	Unit
Thermal Resistance, Junction-to-Ambient <sup>(1)</sup>	$R_{\theta JA}$	62.5	°C/W
Thermal Resistance, Junction-to-Case <sup>(1)</sup>	$R_{\theta JC}$	3.01	

## Ordering Information







Part Number	Temp. Range	Package	Packing	RoHS Status
MDF7N65BTH	-55~150°C	TO-220F	Tube	Halogen Free

## Electrical Characteristics (Ta =25°C)

Characteristics	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static Characteristics</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	I <sub>D</sub> = 250μA, V <sub>GS</sub> = 0V	650	-	-	V
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA	2.0	-	4.0	
Drain Cut-Off Current	I <sub>DSS</sub>	V <sub>DS</sub> = 650V, V <sub>GS</sub> = 0V	-	-	1	μA
Gate Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> = ±30V, V <sub>DS</sub> = 0V	-	-	100	nA
Drain-Source ON Resistance	R <sub>DS(ON)</sub>	V <sub>GS</sub> = 10V, I <sub>D</sub> = 3.5A	-	1.15	1.35	Ω
Forward Transconductance	g <sub>fs</sub>	V <sub>DS</sub> = 30V, I <sub>D</sub> = 3.5A	-	8.5	-	S
<b>Dynamic Characteristics</b>						
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> = 520V, I <sub>D</sub> = 7.0A, V <sub>GS</sub> = 10V <sup>(3)</sup>	-	18.4	-	nC
Gate-Source Charge	Q <sub>gs</sub>		-	4.5	-	
Gate-Drain Charge	Q <sub>gd</sub>		-	6.7	-	
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> = 25V, V <sub>GS</sub> = 0V, f = 1.0MHz	-	786	-	pF
Reverse Transfer Capacitance	C <sub>rss</sub>		-	4.1	-	
Output Capacitance	C <sub>oss</sub>		-	85.4	-	
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>GS</sub> = 10V, V <sub>DS</sub> = 325V, I <sub>D</sub> = 7.0A, R <sub>G</sub> = 25Ω <sup>(3)</sup>	-	13.6	-	ns
Rise Time	t <sub>r</sub>		-	32.6	-	
Turn-Off Delay Time	t <sub>d(off)</sub>		-	57.6	-	
Fall Time	t <sub>f</sub>		-	38	-	
<b>Drain-Source Body Diode Characteristics</b>						
Maximum Continuous Drain to Source Diode Forward Current	I <sub>S</sub>	I <sub>S</sub> = 7.0A, V <sub>GS</sub> = 0V	-	7	-	A
Source-Drain Diode Forward Voltage	V <sub>SD</sub>		-	-	1.4	V
Body Diode Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> = 7.0A, di/dt = 100A/μs	-	280	-	ns
Body Diode Reverse Recovery Charge	Q <sub>rr</sub>		-	4.3	-	μC

Note :

1. Pulse width is based on R<sub>θJC</sub> & R<sub>θJA</sub> and the maximum allowed junction temperature of 150°C.
2. Pulse test: pulse width ≤300us, duty cycle≤2%, pulse width limited by junction temperature T<sub>J(MAX)</sub>=150°C.
3. I<sub>SD</sub> ≤7.0A, di/dt≤200A/us, V<sub>DD</sub>=50V, R<sub>g</sub> =25Ω, Starting T<sub>j</sub>=25°C
4. L=8.0mH, I<sub>AS</sub>=7.0A, V<sub>DD</sub>=50V, R<sub>g</sub> =25Ω, Starting T<sub>j</sub>=25°C,






Fig.7 Gate Charge Characteristics




Fig.8 Capacitance Characteristics




Fig.9 Maximum Safe Operating Area  
MDF7N65B(TO-220F)




Fig.10 Transient Thermal Response Curve  
MDF7N65B(TO-220F)




Fig.11 Single Pulse Maximum Power Dissipation





Fig.12 Maximum Drain Current vs. Case Temperature

## Physical Dimensions

### 3 Leads, TO-220F

Dimensions are in millimeters unless otherwise specified



Symbol	Min	Nom	Max
A	4.50		4.93
b	0.63		0.91
b1	1.15		1.47
C	0.33		0.63
D	15.47		16.13
E	9.60		10.71
e		2.54	
F	2.34		2.84
G	6.48		6.90
L	12.24		13.72
L1	2.79		3.67
Q	2.52		2.96
Q1	3.10		3.50
ØR	3.00		3.55

**DISCLAIMER:**

The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

MagnaChip reserves the right to change the specifications and circuitry without notice at any time. MagnaChip does not consider responsibility for use of any circuitry other than circuitry entirely included in a MagnaChip product. [MagnaChip®](#) is a registered trademark of MagnaChip Semiconductor Ltd.