


HEADSET MICROPHONE


XS 1300 has an ergonomic design and a robust fixation system. It is suitable for live shows as it goes unnoticed and provides total freedom of movement on stage.




Technical Specifications

Type	Condenser
Cartridge Diameter	∅ 4 mm
Polar Pattern	Omnidirectional
Sensitivity	18mv/Pa(-45dB±3dB)
Frequency Response	100 Hz – 20 kHz
Impedance	1KΩ±30%
Power Supply	2.0V – 10V DC
S/N Ratio	≥58dB
Cable length	1.2 m
Connector type	3.5 mm male screw

Frequency Response



Polar Pattern



MICRÓFONO DE CABEZA


XS 1300 tiene un diseño ergonómico y un firme sistema de fijación. Es adecuado para espectáculos en vivo ya que pasa desapercibido y ofrece total libertad de movimiento en el escenario.



Especificaciones Técnicas

Tipo	Condensador electret
Diámetro de la cápsula	∅ 4 mm
Patrón Polar	Omnidireccional
Sensibilidad	18mv/Pa(-45dB±3dB)
Respuesta en frecuencia	100 Hz – 20 kHz
Impedancia	1KΩ±30%
Alimentación	2.0V – 10V DC
Relación S/N	≥58dB
Longitud del cable	1.2 m
Tipo de conector	Rosca macho de 3.5 mm

Frequency Response



Polar Pattern

